



# SAREGO

DESCRIPTION: Medium, leather-like grain with pearlized finish.

APPLICATIONS: Hospitality, Contract, Commercial

## GENERAL SPECIFICATIONS:

**Material width:** 55"  
**Thickness:** 1.00 mm.  
**Weight:** 31 ounces per linear yard +/- 5%  
**Roll Size:** 35 yards approx.  
**Composition Surface:** 100% PVC  
**Composition Backing:** 35% COT, 65% PES

## PERFORMANCE SPECIFICATIONS:

**Abrasion:** Martindale >50,000 cycles High Traffic/Public Spaces  
**Colorfastness to light:** Xeno Test – blue scale Class 7.0 40 hr.  
**Phthalate Free**

**Flammability:** California Fire Code Technical Bulletin No. 117 -2013 Section 1, NFPA 260

## CLEANING INSTRUCTIONS:

Cleaning Code – W Water /soap

Preventing dust buildup will keep vinyl coverings looking their best. Regular dusting and wiping the surface with damp non-abrasive soft cloth is all that is needed to keep this material looking great. For most stains, spot clean with water and mild soap. Gently dab the vinyl taking care not to scratch the surface of the vinyl. Remove the soapy solution by wiping it off with water dampened clean soft cloth. Dry with soft lint-free cloth. We recommend prompt cleaning of any soiled area.

### Please Note:

Before using recommended cleaners above, it is advisable to test first in an inconspicuous area. Other cleaning agents are not recommended for use. They may contain harsh or unknown solvents and are subject to formula changes without notice. These solvents may damage the plasticizers which keep the vinyl soft causing it to crack or discolor. Never use harsh solvents intended for industrial application. Always use a soft, clean white cloth to clean stained or soiled areas. Avoid use of paper towels and never use abrasives such as steel wool and powdered abrasive cleaners. Never use methanol or ethanol alcohol or hard surface cleaners on vinyl upholstery.

Lilly Kral reserves the right to make change without notice